

# Pro L1505UHNL WUXGA 3LCD Laser Projector With 4K Enhancement<sup>1</sup> Without Lens



Product shown with lens. Lens sold separately.

## Premium large-venue laser projector with 4K Enhancement<sup>1</sup>.

**Bright, vivid color** — 12,000 lumens color/white brightness<sup>2</sup>

**Exceptional Full HD widescreen display** — native WUXGA (1920 x 1200) with 4K Enhancement<sup>1</sup> for presentations, videos, digital signage and more

**Solid-state laser light source** — virtually maintenance-free 20,000-hour laser light source with no lamps $^{3}$ 

**Dynamic projection capabilities** — advanced built-in Edge Blending, image warping and curved-surface correction technologies for a variety of applications

**Advanced connectivity** — 3G-SDI, HDBaseT™, HDMI®, DVI-D, VGA, 5-BNC and Stereo Mini

Nine optional interchangeable lenses (sold separately) — with powered lens shift and lens memory

 $\begin{tabular}{l} \textbf{Installation flexibility} - 360\end{tabular} - 360\end{tabular} - degree projection and Portrait Mode for added versatility$ 

**Remote management and control tools** — included software allows for web-based monitoring and control of Epson® networked projectors

**Image correction camera** — automatically adjusts color and brightness to match other projectors in multiple-screen applications

**Brightness lock feature** — allows users to securely set maximum brightness level









### Pro L1505UHNL WUXGA 3LCD Laser Projector With 4K Enhancement Without Lens

#### **Specifications**

Projection System High-aperture Epson 3LCD, 3-chip

Projection Method Front/rear/ceiling mount **Driving Method** Poly-silicon TFT Active Matrix

Pixel Number 2,304,000 dots (1920 x 1200) x 3 Native Resolution 1920 x 1200 (WUXGA) Resize 1280 x 1024, 1400 x 1050

Aspect Ratio 16:10, 16:9, 4:3 **Pixel Arrangement Cross stripe** 

Color Brightness<sup>2</sup> Color Light Output: 12,000 lumens White Brightness<sup>2</sup> White Light Output: 12,000 lumens

Contrast Ratio 2,500,000:1 **Brightness Uniformity (Typical)** 90% Color Reproduction Up to 1 billion colors Size (Projected Distance) 60" - 500"

Lens Shift Vertical: ±60 percent; horizontal: ±18 percent Keystone Correction Vertical: ±45 degrees; horizontal: ±30 degrees

Illumination Technology Laser Diode

**Light Source Life<sup>3</sup>** 

20,000 hours (Normal) 30,000 hours (Extended)

#### **Projection Lens (Standard, Not Included)**

See website for information on optional lenses.

Type Powered shift/focus/zoom **F-number** 1.8 - 2.35

Focal Length 36.0 - 57.35 mm Zoom Ratio Optical zoom 1 - 1.61 Throw Ratio Range 1.57 - 2.56

#### Other Features

Operating Temperature 32 ° to 113 ° F (0 ° to 45 ° C) Power Supply Voltage  $100 - 240 \text{ V} \pm 10\%$ , 50/60 Hz AC

**Power Consumption** 955 W (Normal Mode) 597 W (Extended Mode) 2.0 W Standby (Communication on) 0.3 W Standby (Communication off)

Fan Noise 39 dB (Normal Mode); max. 30 dB (Quiet Mode) Security Security cable hole, lens lock, Kensington

#### Interfaces

3G-SDI x 1 DVI-D x 1 HDMI x 1 HDBaseT x 1 5-BNC VGA x 1

Audio in: Mini Stereo x 3 Variable audio out: Mini Stereo x 1 USB connector Type B x 1: For service only USB connector Type A x 1: For wireless only Monitor out: Mini D-sub 15 pin x 1

Serial: RS-232c x 1



#### **Effective Scanning Frequency Range**

Pixel Clock 13.5 MHz - 162 MHz (up to UXGA 60 Hz)

Horizontal 15 kHz - 92 kHz Vertical 50 Hz - 85 Hz

#### Video I/O

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-AL/PAL60/ SECAM/480i/576i/480p/576p/720p/1080i/1080p/UDH/4K Pixelworks® Video Chip 3D Y/C separation, noise reduction motion compensated Interlace-Progressive conversion (2 - 2.3 - 2 film detection)

#### Dimensions (W x D x H)

Including Feet, Lens 23.1" x 8.3" x 19.4" Weight 52.2 lb (with standard lens, not included)

#### **Remote Control**

Features Power, search selection, lens shift, zoom, focus, test pattern selection, A/V Mute, freeze, user ID, auto, aspect, color mode, help, menu, enter, esc and standby

#### **Operating Angle**

Right/left: Front: ± 60 degrees, Rear: ± 30 degrees Upper/lower: Front: ± 20 degrees, Rear: +10 to +50 degrees Operating Distance 49 ft

#### **Eco Features**

RoHS compliant Recyclable product4

Epson America, Inc. is a SmartWay® Transport Partner<sup>5</sup>

#### Support

#### Epson Connection<sup>SM</sup>

Pre-sales support: U.S. and Canada 800-442-1977 Internet website: www.epson.com

#### **Service Programs**

The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

Epson Road Service program, PrivateLine® dedicated toll-free support (U.S. and Canada only)

#### What's in the Box

Pro L1505UHNL projector, power cable, projector remote control with batteries, cable cover, HDMI cable clamp

#### **Ordering Information**

Pro L1505UHNL V11H910820 Replacement Air Filter (ELPAF51) V13H134A51 Ultra Short-throw Lens (ELPLX02) V12H004X02 V12H004U03 Short-throw #1 Zoom Lens (ELPLU03) Short-throw #2 Zoom Lens (ELPLU04) V12H004U04 V12H004W05 Wide-throw #1 Zoom Lens (ELPLW05) Wide-throw #2 Zoom Lens (ELPLW06) V12H004W06 Middle-throw #2 Zoom Lens (ELPLM15) V12H004M0F Middle-throw #3 Zoom Lens (ELPLM10) V12H004M0A Middle-throw #4 Zoom Lens (ELPLM11) V12H004M0B V12H004L08 Long-throw Zoom Lens (ELPLL08) Epson Ceiling Mount – Low Ceilings (ELPMB47) V12H802010 Epson Ceiling Mount – High Ceilings (ELPMB48) V12H803010 HDBaseT Transmitter (ELPHD01) V12H547020 Wireless LAN Module (ELPAP10) V12H731P02 1-year Extended Warranty EPPEXPC1 2-year Extended Warranty EPPEXPC2

1 4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with IDMS 15.4; w assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. The projector has a limited warranty of three years or 20,000 hours, whichever comes first. | 4 For convenient and reasonable recycling options, visit www.epson.com/recycle | 5 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

**Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2019 Epson America, Inc. Com-SS-Oct-13 CPD-54448R2 6/19

#### Contact: