



Specifications

SMART electric height-adjustable mobile stand

Model FSE-410


Overview

Designed for the current line of SMART Board® interactive displays in North America, the SMART electric height-adjustable mobile stand features 26" (66 cm) of powered height adjustment. Safety features include a safety stop mechanism that reverses direction briefly if an obstruction is encountered and a controller that locks height adjustment automatically to ensure that only people with proper training or supervision can use the stand. With its wide footprint and sturdy steel frame, the stand supports displays up to 86" (218 cm) diagonal that weigh up to 200 lb. (91 kg). The stand supports a maximum weight of 240 lb. (111 kg) with a display and accessories. You can easily roll the stand across smooth floors and secure it in place with the industrial grade 4" locking casters. The stand has a UL-certified drive system, is certified to UL 962 for Usage Area II, and complies with Americans with Disabilities Act (ADA) standards. It also includes VESA mounting points for easy installation of the display and peripherals, a locking storage cabinet, and a surge-protected power bar.

See smarttech.com for more information about this product.

Dimensions and weights1

Dimensions



Weight

106 lb. (48 kg)

Shipping dimensions

 $45 2/8" \times 32 5/8" \times 7 3/8"$ (115 cm × 83 cm × 19 cm)

Shipping weight

115 lb. (52.5 kg)

Storage cabinet dimensions

29 1/2" × 19 5/8" × 7 1/8" (75 cm × 50 cm × 18.1 cm)

smarttech.com/kb/171626

 $^{^{1}}$ All dimensions $\pm 1/8$ " (0.3 cm). All weights ± 2 lb. (0.9 kg).

SMART electric height-adjustable mobile stand – Model FSE-410

Specifications

Hardware

displays

Supported SMART Board SMART Board GX series

SMART Board MX, MX (V2), and MX Pro series SMART Board 6000 and 6000 Pro series SMART Board 6000S and 6000S Pro series

SMART Board 7000, 7000 Pro series SMART Board 7000R and 7000R Pro series

SMART Board 2000 series

Maximum display size

Supports displays up to 86" (218 cm) diagonal and 80" (203 cm) wide

Maximum display

200 lb. (91 kg)

weight

240 lb. (111 kg)

Maximum total weight (display and accessories)

Height adjustment

26" (66 cm) Range

Maximum extended

74" (188 cm)

height

Minimum extended height

48" (122 cm)

Components

4" industrial-grade locking casters Wheels

VESA® mounting pattern: 300 mm × 400 mm - M8, 500 mm × 400 mm - M8, 600 mm × 400 mm -Mounting

M8, 700 mm × 400 mm - M8, 400 mm × 200 mm - M8, 800 mm × 200 mm - M8 with adapter (not

included)

Storage and operating requirements

Power consumption

100V-240V AC, 50 -60 Hz Supply voltage

110V AC, 220V AC Nominal voltage

(!) Important

The supplied power bar can only be used with 120V input.

Power consumption

Raising a display (maximum load) 300 W

Standby mode

0.1 W

smarttech.com/kb/171626 2

SMART electric height-adjustable mobile stand – Model FSE-410

Specifications

Duty cycle 10% (2 minutes of operation fully loaded, 18 minutes of rest)

Operating

50-104°F (10-40°C)

temperature

Storage temperature 14-158°F (-10-70°C)

Humidity 85% non-condensing

Certification and compliance

Regulatory certification

FCC, ISED, UL Listed - U.S. and Canada UL 962 - Usage Area II

Other ADA

Environmental compliance

European Union RoHS, REACH and Packaging Directive

U.S. CONEG Packaging, California proposition 65

Purchasing information

Order numbers

FSE-410 SMART electric height-adjustable mobile stand

FSE-400-HL Handles

 $8" \times 6" \times 4"$ (20.3 cm × 15.2 cm × 10.2 cm)

1 lb. 8 oz. (0.7 kg)

FSE-400-CH Cable hook

 $8" \times 6" \times 4"$ (20.3 cm × 15.2 cm × 10.2 cm)

1 lb. (0.5 kg)

FSE-400-LS Laptop shelf

Optional accessories See <u>smarttech.com/accessories</u>

Warranty Five-year limited equipment warranty

smarttech.com/support smarttech.com/contactsupport

© 2020–2022 SMART Technologies ULC. All rights reserved. SMART Board, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. February 7, 2022.

smarttech.com/kb/171626 3