

## **ViewSonic VB-CAM-201**

<b>Sensor</b>	1/2.5 inch, CMOS, 8.51M pixel
<b>Lens</b>	5x digital zoom, pan/tilt $\pm 15^\circ$
<b>Digital Noise Reduction</b>	2D, 3D digital noise reduction
<b>White Balance</b>	Automatic, Indoor, Outdoor, One Push, Manual
<b>Field of View (FOV)</b>	120° (DFOV), 110° (HFOV)
<b>Backlight Compensation</b>	Yes
<b>Resolution</b>	3840 x 2160
<b>PTZ</b>	MPT + EPTZ
<b>HDMI 2.0 Out</b>	1
<b>USB 2.0 Type A</b>	1
<b>USB 3.0 Type C</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>Video Support</b>	4K@30fps, 1080P@60fps, 1080P@30fps, 720P@60fps, 720P@30fps, etc.
<b>Compression</b>	H.264 / MJPEG /YUY2 /NV12
<b>Internal Speakers</b>	8W (x1)
<b>Sensitivity</b>	96dB at 0.5m / 1.6 ft
<b>Audio features</b>	32K sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto Noise suppression / Auto Gain control
<b>USB protocol</b>	Support UAC 2.0
<b>Microphone</b>	Beamforming microphone
<b>Microphone array</b>	4 microphones

<b>Distance</b>	6m / 20 ft
<b>Minimum Hardware Specs</b>	CPU (Recommended) 2.4GHz Intel® Core 2™ Duo processor or higher, RAM (Recommended) 2GB of Memory or higher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video output
<b>Voltage</b>	DC 12V/1.5A Adapter
<b>Consumption (typical)</b>	18W
<b>Bluetooth</b>	Bluetooth 5.0
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>Packaging (in.)</b>	26.54 x 18.98 x 18.66
<b>Physical (in.)</b>	23.62 x 5.31 x 4.53
<b>Packaging (mm)</b>	674 x 482 x 474
<b>Physical (mm)</b>	600 x 135 x 115
<b>Net (lbs)</b>	4.86
<b>Gross (lbs)</b>	28.66
<b>Gross (kg)</b>	4.86
<b>Warranty</b>	One-year limited warranty on parts and labor
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Regulations</b>	FCC, FCC ID, CE, IC ID, LVD
<b>PACKAGE CONTENTS</b>	VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6